



DATA SHEET SWISSCAVE WIB-88DFP

Technical Data

Exterior		Performance data	
Casing	Black coated steel	Bottle capacity	40
Door glazing	Fully glazed UV-resistant, gas-filled, with low energy panes equipped glass door (double glazed) ready for panel mounting	Space for oversized bottles (Magnum, 3lt.)	Yes, on bottom level
Door frame	Filigree edging made of black anodised, brushed aluminium	Humidity	Recommendation 50-70%
Door handle	Yes (panel-mountable)	Actively managed humidity (adjustment range 60-80%)	Nein
Door lock	No	Climate classification	SN-T
Door hinge	Right	Volume	100 l
Door hinge convertible as option (right to left)	Yes	Noise level	40 dB(A) sound-absorbing recommendation
Product dimensions without door handle (H/W/D)	877 x 559 x 554 mm	Temperature range lower zone	5 °C - 20 °C
Packaging dimensions (H/W/D)	975 x 655 x 640 mm	Temperature range upper zone	5 °C - 20 °C
		Temperature delta between zones	2 °C
Interior		General Information	
Temperature zones	2	Cooler shape	Kitchen-built-in
Lighting	All around illumination white, blue, amber (adjustable)	Maintenance contract (warranty extension)	Recommended
Lighting on/off switch	Yes	Transport weight	59 kg
Number of shelves total	5	Net weight	50 kg
Number of display shelves	0 (optional available)	Power consumption per day	0.345 kWh (ca.)
Shelf material	Raw natural sapele (Mahogany) wooden display shelves with attractive grip bars	Voltage	220 V / 50 Hz
Telescopic shelves on extendable steel ball bearings	Full extension shelves (80%)	Cable length	2 m
Inside casing	Black PUR		
Scope of functions			
Optimal usage	Storing and aging of wine		
User interface	2 digital displays (set and actual temp.)		
Active carbon filters (ensuring optimal air quality)	Yes		
Compressor	Embraco inverter compressor		
Coolant	R600a (environment friendly)		
Vibrationfree implementation	Yes		
Cooling system	Combined fan and convection cooling		
Defrost function	Automatic		
Temperatur Memory Function (Power failure)	Yes		
Condensation water container	Yes		
Heating	Powerful winter heating function (*In heating mode, temperature and humidity values may vary from the set value)		
Acoustic temperature alarm	Yes		
Acoustic door alarm	Yes		
Feet adjustable to compensate uneven floors	Yes		



SWISSCAVE AG WIB-88DF

A
B
C
D
E
F
G

126 kWh/annum

42

40dB
ABCD

20/19/2018